2017 SUPER DUTY F-SERIES TRUCKS

Order Guide Supplemental Reference

4/13/17

This supplement contains Maximum Payload Charts, Snow Plow Application Charts, Cab-to-Axle dimensions and Spring Selection Charts.

This information will help you in selecting the right truck to meet your customers' needs.

Please refer to the appropriate 2017 eSourceBook section for more complete weight rating information.

CONTENTS

Payload Package Selection Charts

- F-250 SRW Pickup 1
- F-350 SRW Pickup 2
- F-350 DRW Pickup 3
- F-450 DRW Pickup 4
- F-350 SRW Chassis Cab 5
- F-350 DRW Chassis Cab 6
- F-450 Chassis Cab 7
- F-550 Chassis Cab 8

Snow Plow Applications Charts 9

Cab-to-Axle Dimension Chart 10

Front Spring/GAWR Selection Charts

- F-250 SRW Pickup 11
- F-350 SRW Pickup/Pickup Box Delete 12
- F-350 DRW Pickup/Pickup Box Delete 13
- F-450 DRW Pickup 14
- F-350 SRW Chassis Cab 15
- F-350 DRW Chassis Cab 16
- F-450 Chassis Cab 17
- F-550 Chassis Cab 18

2017 SUPER DUTY F-SERIES TRUCKS

MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

5/24/2016

F-250 Pickup
Standard GVWR

	Cab	Regular Cab		SuperCab				Crew Cab			
	Wheelbase	141.6"		148.0"		164.2"		159.8"		176.0"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	9,950	4,200	10,000	4,000	10,000	3,910	10,000	3,880	10,000	3,640
	6.7L	10,000	3,440	10,000	3,180	10,000	3,110	10,000	3,080	10,000	2,820
4x4	6.2L	10,000	3,830	10,000	3,560	10,000	3,490	10,000	3,450	10,000	3,230
	6.7L	10,000	3,040	10,000	2,770	10,000	2,690	10,000	2,660	10,000	2,430

F-250 Pickup
Optional GVWR

	Cab	Regular Cab		SuperCab				Crew Cab			
	Wheelbase	141.6"		148.0"		164.2"		159.8"		176.0"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	9,900	4,150	9,900	3,900	9,900	3,810	9,900	3,780	9,900	3,540
	6.7L	9,900	3,340	9,900	3,080	9,900	3,010	9,900	2,980	9,900	2,720
4x4	6.2L	9,900	3,730	9,900	3,460	9,900	3,390	9,900	3,350	9,900	3,130
	6.7L	9,900	2,940	9,900	2,670	9,900	2,590	9,900	2,560	9,900	2,330

2017 SUPER DUTY F-SERIES TRUCKS
MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS
5/24/2016

F-350 SRW Pickup
Standard Variable GVWR for 17" Wheel & Tire

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase		141.6"		148.0"		164.2"		159.8"		176.0"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	10,000	4,030	10,000	3,810	10,300	3,990	10,100	3,750	10,500	3,910
	6.7L	10,600	3,880	10,800	3,870	11,000	3,940	10,900	3,790	11,100	3,760
4x4	6.2L	10,300	3,900	10,400	3,790	10,700	3,980	10,500	3,740	10,800	3,800
	6.7L	11,000	3,850	11,100	3,750	11,300	3,830	11,200	3,680	11,500	3,740

F-350 SRW Pickup
Standard Variable GVWR for 18" Wheel & Tire

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase		141.6"		148.0"		164.2"		159.8"		176.0"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	10,400	4,370	10,500	4,250	10,800	4,430	10,600	4,200	10,900	4,260
	6.7L	11,100	4,320	11,200	4,220	11,500	4,380	11,300	4,130	11,500	4,100
4x4	6.2L	10,800	4,340	10,800	4,130	11,200	4,420	10,900	4,080	11,300	4,240
	6.7L	11,500	4,300	11,500	4,100	11,500	3,970	11,500	3,930	11,500	3,680

F-350 SRW Pickup
Standard Variable GVWR for 18"/20" All-Terrain & 20" All-Season Tire 4x4

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase		141.6"		148.0"		164.2"		159.8"		176.0"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x4	6.2L	11,300	4,830	11,300	4,620	11,500	4,710	11,300	4,470	11,500	4,440
	6.7L	11,500	4,290	11,500	4,090	11,500	3,960	11,500	3,920	11,500	3,680

F-350 SRW Pickup
Optional Fixed 10,000-lb. GVWR

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase		141.6"		148.0"		164.2"		159.8"		176.0"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	10,000	3,930	10,000	3,710	10,000	3,690	10,000	3,650	10,000	3,410
	6.7L	10,000	3,280	10,000	3,070	10,000	2,940	10,000	2,890	10,000	2,660
4x4	6.2L	10,000	3,600	10,000	3,390	10,000	3,280	10,000	3,240	10,000	3,000
	6.7L	10,000	2,850	10,000	2,650	10,000	2,530	10,000	2,480	10,000	2,240

F-350 SRW Pickup
Optional Fixed 9900-lb. GVWR

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase		141.6"		148.0"		164.2"		159.8"		176.0"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	9,900	3,930	9,900	3,710	9,900	3,590	9,900	3,550	9,900	3,310
	6.7L	9,900	3,180	9,900	2,970	9,900	2,840	9,900	2,790	9,900	2,560
4x4	6.2L	9,900	3,500	9,900	3,290	9,900	3,180	9,900	3,140	9,900	2,900
	6.7L	9,900	2,750	9,900	2,550	9,900	2,430	9,900	2,380	9,900	2,140

F-350 SRW Pickup
Optional GVWR Downgrade 17" Tire

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase		141.6"		148.0"		164.2"		159.8"		176.0"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x4	6.7L	---	---	---	---	---	---	---	---	11,400	3,640

F-350 SRW Pickup
Optional GVWR Downgrade 18" All-Season Tire

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase		141.6"		148.0"		164.2"		159.8"		176.0"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.7L	---	---	---	---	11,400	4,280	---	---	11,400	4,000
4x4	6.7L	11,400	4,200	11,400	4,000	11,400	3,870	11,400	3,830	11,400	3,580

F-350 SRW Pickup
Standard Variable GVWR for18"/20" All-Terrain & 20" All-Season Tire 4x4

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase		141.6"		148.0"		164.2"		159.8"		176.0"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x4	6.2L	---	---	---	---	11,400	4,610	---	---	11,400	4,340
	6.7L	11,400	4,190	11,400	3,990	11,400	3,860	11,400	3,820	11,400	3,580

2017 SUPER DUTY F-SERIES TRUCKS

MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

5/24/2016

F-350 DRW Pickup
Maximum GVWR

Cab		Regular Cab		Super Cab				Crew Cab			
Wheelbase		141.6"		148.0"		164.2"		159.8"		176.0"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	14,000	7,630	---	---	14,000	7,200	---	---	14,000	6,950
	6.7L	14,000	6,850	---	---	14,000	6,460	---	---	14,000	6,220
4x4	6.2L	14,000	7,160	---	---	14,000	6,780	---	---	14,000	6,540
	6.7L	14,000	6,430	---	---	14,000	6,050	---	---	14,000	5,820

F-350 DRW Pickup Box Delete
Maximum GVWR

Cab		Regular Cab		Super Cab				Crew Cab			
Wheelbase		141.6"		148.0"		164.2"		159.8"		176.0"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.7L	13,000	6,270	---	---	13,000	5,880	---	---	13,000	5,650
4x4	6.7L	13,000	5,850	---	---	13,000	5,470	---	---	13,000	5,240

2017 SUPER DUTY F-SERIES TRUCKS

MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

5/24/2016

F-450 DRW Pickup

Standard GVWR

Cab		Crew Cab	
Wheelbase		176.0"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)
4x4	6.7L	14,000	5,320

2017 SUPER DUTY F-SERIES TRUCKS

MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

5/24/2016

F-350 SRW Chassis Cab
Optional Fixed 9800-lb. GVWR

		Regular Cab								Super Cab		Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	9,800	4,370	---	---	---	---	---	---	9,800	4,070	9,800	3,830	---	---
	6.7L	9,800	3,630	---	---	---	---	---	---	9,800	3,280	9,800	3,040	---	---
4x4	6.2L	9,800	3,960	---	---	---	---	---	---	9,800	3,640	9,800	3,420	---	---
	6.7L	9,800	3,190	---	---	---	---	---	---	9,800	2,850	9,800	2,620	---	---

F-350 SRW Chassis Cab
Optional Fixed 10,000-lb. GVWR

		Regular Cab								Super Cab		Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	10,000	4,520	---	---	---	---	---	---	10,000	4,220	10,000	3,980	---	---
	6.7L	10,000	3,780	---	---	---	---	---	---	10,000	3,430	10,000	3,190	---	---
4x4	6.2L	10,000	4,110	---	---	---	---	---	---	10,000	3,790	10,000	3,560	---	---
	6.7L	10,000	3,340	---	---	---	---	---	---	10,000	2,990	10,000	2,770	---	---

F-350 SRW Chassis Cab
Standard/Variable GVWR for 18" Wheels/Tires

		Regular Cab								Super Cab		Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	10,500	4,870	---	---	---	---	---	---	10,900	4,970	11,000	4,830	---	---
	6.7L	11,100	4,730	---	---	---	---	---	---	11,500	4,780	11,500	4,540	---	---
4x4	6.2L	10,900	4,860	---	---	---	---	---	---	11,300	4,940	11,400	4,820	---	---
	6.7L	11,500	4,690	---	---	---	---	---	---	11,500	4,350	11,500	4,120	---	---

2017 SUPER DUTY F-SERIES TRUCKS

MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

5/24/2016

F-350 DRW Chassis Cab
Standard Fixed GVWR

		Regular Cab				Super Cab				Crew Cab			
		60" CA		84" CA		60" CA				60" CA			
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)			GVWR (lbs)	Max Payload (lbs)		
4x2	6.2L	14,000	8,020	14,000	7,330	14,000	7,700	---	---	14,000	7,480	---	---
	6.7L	14,000	7,240	14,000	7,150	14,000	6,360	---	---	14,000	6,720	---	---
4x4	6.2L	14,000	7,560	14,000	6,880	14,000	7,220	---	---	14,000	7,040	---	---
	6.7L	14,000	6,790	14,000	6,690	14,000	5,900	---	---	14,000	6,280	---	---

2017 SUPER DUTY F-SERIES TRUCKS

MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

5/24/2016

F-450 DRW Chassis Cab
Standard Fixed 16,500 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)
4x2	6.8L	16,500	9,930	16,500	9,820	16,500	9,670	16,500	9,570	16,500	9,650	16,500	9,430	16,500	9,440	16,500	9,360
	6.7L	16,500	9,170	16,500	9,010	16,500	8,830	16,500	8,730	16,500	8,850	16,500	8,640	16,500	8,620	16,500	8,530
4x4	6.8L	16,500	9,610	16,500	9,480	16,500	9,310	16,500	9,250	16,500	9,300	16,500	9,130	16,500	9,080	16,500	9,010
	6.7L	16,500	8,820	16,500	8,650	16,500	8,510	16,500	8,380	16,500	8,460	16,500	8,290	16,500	8,240	16,500	8,180

F-450 DRW Chassis Cab
Optional Fixed 15,000 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	15,000	8,430	15,000	8,320	15,000	8,170	15,000	8,070	15,000	8,150	15,000	7,930	15,000	7,940	15,000	7,860
	6.7L	15,000	7,670	15,000	7,510	15,000	7,330	15,000	7,230	15,000	7,350	15,000	7,140	15,000	7,120	15,000	7,030
4x4	6.8L	15,000	8,110	15,000	7,980	15,000	7,810	15,000	7,750	15,000	7,800	15,000	7,630	15,000	7,580	15,000	7,510
	6.7L	15,000	7,320	15,000	7,150	15,000	7,010	15,000	6,880	15,000	6,960	15,000	6,790	15,000	6,740	15,000	6,680

F-450 DRW Chassis Cab
Optional Fixed 16,000 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	16,000	9,430	16,000	9,320	16,000	9,170	16,000	9,070	16,000	9,150	16,000	8,930	16,000	8,940	16,000	8,860
	6.7L	16,000	8,670	16,000	8,510	16,000	8,330	16,000	8,230	16,000	8,350	16,000	8,140	16,000	8,120	16,000	8,030
4x4	6.8L	16,000	9,110	16,000	8,980	16,000	8,810	16,000	8,750	16,000	8,800	16,000	8,630	16,000	8,580	16,000	8,510
	6.7L	16,000	8,320	16,000	8,150	16,000	8,010	16,000	7,880	16,000	7,960	16,000	7,790	16,000	7,740	16,000	7,680

2017 SUPER DUTY F-SERIES TRUCKS

MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

5/24/2016

F-550 DRW Chassis Cab
Standard 18,000 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	18,000	11,430	18,000	11,320	18,000	11,170	18,000	11,070	18,000	11,150	18,000	10,930	18,000	10,940	18,000	10,860
	6.7L	18,000	10,670	18,000	10,510	18,000	10,330	18,000	10,230	18,000	10,350	18,000	10,140	18,000	10,120	18,000	10,030
4x4	6.8L	18,000	11,110	18,000	10,980	18,000	10,810	18,000	10,750	18,000	10,800	18,000	10,630	18,000	10,580	18,000	10,510
	6.7L	18,000	10,320	18,000	10,150	18,000	10,010	18,000	9,880	18,000	9,960	18,000	9,790	18,000	9,740	18,000	9,680

F-550 DRW Chassis Cab
Optional 17,500 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	17,500	10,930	17,500	10,820	17,500	10,670	17,500	10,570	17,500	10,650	17,500	10,430	17,500	10,440	17,500	10,360
	6.7L	17,500	10,170	17,500	10,010	17,500	9,830	17,500	9,730	17,500	9,850	17,500	9,640	17,500	9,620	17,500	9,530
4x4	6.8L	17,500	10,610	17,500	10,480	17,500	10,310	17,500	10,250	17,500	10,300	17,500	10,130	17,500	10,080	17,500	10,010
	6.7L	17,500	9,820	17,500	9,650	17,500	9,510	17,500	9,380	17,500	9,460	17,500	9,290	17,500	9,240	17,500	9,180

F-550 DRW Chassis Cab
Optional 19,000 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	19,000	12,300	---	---	---	---	---	---	---	---	---	---	---	---	---	---
4x4	6.8L	19,000	11,960	---	---	---	---	---	---	---	---	---	---	---	---	---	---

F-550 DRW Chassis Cab
Optional 19,500 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	---	---	19,500	12,730	19,500	12,560	19,500	12,500	19,500	12,540	19,500	12,390	19,500	12,370	19,500	12,220
	6.7L	19,500	12,000	19,500	11,900	19,500	11,750	19,500	11,700	19,500	11,680	19,500	11,580	19,500	11,460	19,500	11,400
4x4	6.8L	---	---	19,500	12,370	19,500	12,240	19,500	12,120	19,500	12,160	19,500	12,070	19,500	11,930	19,500	11,900
	6.7L	19,500	11,670	19,500	11,560	19,500	11,420	19,500	11,330	19,500	11,370	19,500	11,230	19,500	11,110	19,500	11,060

2017 SUPER DUTY F-SERIES TRUCKS

SNOW PLOW APPLICATION CHARTS

9/30/2016

F-250-450 4x4 Pickup/Box Delete Models (with Driver and One Passenger)

Cab Style	Wheelbase	Engine	F-250 4x4 (17")*	F-350 SRW 4x4 (18")*	F-350 DRW 4x4	F-350 DRW 4x4 (box delete)	F-450 4x4
Regular Cab	141.6"	6.2L V8	100/1005	100/1005	100/1005	X	X
		6.7L V8	100/1005	100/1005	100/1005	100/1005	X
SuperCab	148.0"	6.2L V8	100/1005	100/1005	X	X	X
		6.7L V8	100/950	100/900	X	X	X
	164.2"	6.2L V8	100/1005	100/1005	100/1005	X	X
		6.7L V8	100/800	100/800	100/800	100/800	X
Crew Cab	159.8"	6.2L V8	100/1005	100/1005	X	X	X
		6.7L V8	100/850	100/850	X	X	X
	176.0"	6.2L V8	100/1005	100/1005	100/1005	X	X
		6.7L V8	100/700	100/700	100/650	100/700	100/600

Legend: * Considering max. GAWR and A/T tires. 100/750= Maximum 100 lbs. of permanently attached hardware/maximum 750 lbs. of removable plow blade and hardware. The plow and hardware weight limits are shown based upon a vehicle with 33% Ford option content and 300 lbs for the driver and front-seat passenger (150 lbs each). This chart ONLY shows maximum recommended values.

X = Not recommended for snow plow application. Snow Plow Package not available.

F-350 4x4 and F-450/F-550 4x2/4x4 Chassis Cab Models (with Driver and One Passenger)

Cab Style	Wheelbase/ CA	Engine	F-350 SRW 4X4	F-350 4x4 14,000-lb. GVWR	F-450 4x2 16,500-lb. GVWR	F-450 4x4 16,500-lb. GVWR	F-450 4x2 18,000-lb. GVWR	F-450 4x4 18,000-lb. GVWR	F-550+ 4x2 19,000/ 19,500-lb. GVWR	F-550+ 4x4 19,000/ 19,500-lb. GVWR
Regular Cab	145.3"/60"	6.2L V8	100/1005	100/1005	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	100/950	100/950	100/1350	100/1250	100/1350	100/1200	100/1350	100/1250
	169.3"/84"	6.2L V8	X	100/1005	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	X	100/900	100/1350	100/1250	100/1350	100/1200	100/1350	100/1200
	193.3"/108"	6.2L V8	X	X	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	X	X	100/1350	100/1200	100/1350	100/1150	100/1350	100/1150
	205.3"/120"	6.2L V8	X	X	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	X	X	100/1350	100/1150	100/1350	100/1100	100/1350	100/1150
Super Cab	167.9"/60"	6.2L V8	100/1005	100/1005	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	100/850	100/800	100/1350	100/1250	100/1350	100/1200	100/1350	100/1200
	191.9"/84"	6.2L V8	X	X	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	X	X	100/1350	100/1150	100/1350	100/1100	100/1350	100/1100
Crew Cab	179.8"/60"	6.2L V8	100/1005	100/1005	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	100/800	100/750	100/1350	100/1150	100/1350	100/1150	100/1350	100/1100
	203.8"/84"	6.2L V8	X	X	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	X	X	100/1350	100/1100	100/1300	100/1050	100/1300	100/1050

Legend: 100/750= Maximum 100 lbs. of permanently attached hardware. Maximum 750 lbs. of removable plow blade and hardware (maximum plow system weight is the sum of these). The plow and hardware weight limits are shown based upon a vehicle with maximum buildable option content and 300 lbs for the driver and front-seat passenger (150 lbs each). This chart ONLY shows maximum recommended values.

X = Unavailable vehicle configuration.

2017 SUPER DUTY F-SERIES TRUCKS
CAB-TO-AXLE DIMENSION CHART

5/24/2016

Model	Cab	Wheelbase (in.)	Cab-to-Axle (CA) (in.)	Pickup	Box Delete (1)	Chassis Cab
F-250	Reg. Cab	141.6	56.1	8' Box	Yes	--
	SuperCab	148.0	39.9	6.75' Box	--	--
		164.2	56.1	8' Box	Yes	--
	Crew Cab	159.8	39.9	6.75' Box	--	--
		176.0	56.1	8' Box	Yes	--
F-350	Reg. Cab	141.6	56.1	8' Box	Yes	--
		145.3	60.0	--	--	Yes
		169.3	84.0	--	--	Yes
	Super Cab	148.0	39.9	6.75' Box	--	--
		164.2	56.1	8' Box	Yes	--
		167.9	60.0	--	--	Yes
	Crew Cab	159.8	39.9	6.75' Box	--	--
		176.0	56.1	8' Box	Yes	--
		179.8	60.0	--	--	Yes
F-450	Reg. Cab	145.3	60.0	--	--	Yes
		169.3	84.0	--	--	Yes
		193.3	108.0	--	--	Yes
		205.3	120.0	--	--	Yes
	Super Cab	167.9	60.0	--	--	Yes
		191.9	84.0	--	--	Yes
	Crew Cab	176.0	56.0	8' Box	--	--
		179.8	60.0	--	--	Yes
		203.8	84.0	--	--	Yes
F-550	Reg. Cab	145.3	60.0	--	--	Yes
		169.3	84.0	--	--	Yes
		193.3	108.0	--	--	Yes
		205.3	120.0	--	--	Yes
	Super Cab	167.9	60.0	--	--	Yes
		191.9	84.0	--	--	Yes
	Crew Cab	179.8	60.0	--	--	Yes
		203.8	84.0	--	--	Yes

(1) Box Delete available on 8' box only

2017 SUPER DUTY F-SERIES TRUCKS

Front GAWR Selection Chart

3/24/2017

F-250 Pickup/Pickup Box Delete

Cab Style/ Drive/WB (in.)	Engine	Front GAWR (lbs.) STANDARD		Heavy Duty Front Suspension Package (lbs.) 5250-lb. Maximum (4x2) 5990-lb. Maximum (4x4)	Camper Package (lbs.) 5250-lb. Maximum (4x2) 5990-lb. Maximum (4x4)	Snow Plow Package (lbs.)
		MINIMUM	MAXIMUM			
Regular Cab	6.2L	3800	3950	1 UP	2 UP	---
4x2/141.6	6.7L	4400	4550	1 UP	2 UP	---
Regular Cab	6.2L	4400	4400	1 UP	1 UP	5600
4x4/141.6	6.7L	4800	4800	1 UP	1 UP	5990
SuperCab	6.2L	3800	4100	1 UP	2 UP	---
4x2/148.0	6.7L	4550	4700	1 UP	2 UP	---
SuperCab	6.2L	4100	4400	1 UP	2 UP	---
4x2/164.2	6.7L	4850	5250	1 UP	2 UP	---
SuperCab	6.2L	4400	4800	1 UP	1 UP	5600
4x4/148.0	6.7L	4800	5200	1 UP	1 UP	5990
SuperCab	6.2L	4800	4800	1 UP	2 UP	5600
4x4/164.2	6.7L	5200	5600	1 UP	2 UP	5990
Crew Cab	6.2L	3950	4250	1 UP	2 UP	---
4x2/159.8	6.7L	4550	4850	1 UP	2 UP	---
Crew Cab	6.2L	4250	4550	1 UP	2 UP	---
4x2/176.0	6.7L	4850	5250	1 UP	2 UP	---
Crew Cab	6.2L	4400	4800	1 UP	1 UP	5600
4x4/159.8	6.7L	5200	5200	1 UP	1 UP	5990
Crew Cab	6.2L	4800	5200	1 UP	1 UP	5990
4x4/176.0	6.7L	5200	5600	1 UP	1 UP	5990

Please refer to the Body Builder's Guide for further information regarding front GAWR.

2017 SUPER DUTY F-SERIES TRUCKS
Front GAWR Selection Chart

3/24/2017

F-350 SRW Pickup/Pickup Box Delete

Standard/Variable GVWR for 17" Wheel & Tire

Cab Style/ Drive/WB (in.)	Engine	Front GAWR (lbs.) STANDARD		Heavy Duty Front Suspension Package (lbs.) 5250-lb. Maximum (4x2) 5990-lb. Maximum (4x4)	Camper Package (lbs.) 5250-lb. Maximum (4x2) 5990-lb. Maximum (4x4)	Snow Plow Package (lbs.)
		MINIMUM	MAXIMUM			
Regular Cab	6.2L	3800	3950	1 UP	2 UP	
4x2/141.6	6.7L	4400	4550	1 UP	2 UP	---
Regular Cab	6.2L	4400	4400	1 UP	1 UP	5600
4x4/141.6	6.7L	4800	5200	1 UP	1 UP	5990
SuperCab	6.2L	3950	4250	1 UP	2 UP	---
4x2/148.0	6.7L	4550	4700	1 UP	2 UP	---
SuperCab	6.2L	4250	4400	1 UP	2 UP	---
4x2/164.2	6.7L	4850	5000	1 UP	2 UP	---
SuperCab	6.2L	4400	4800	1 UP	1 UP	5600
4x4/148.0	6.7L	4800	5200	1 UP	1 UP	5990
SuperCab	6.2L	4800	4800	1 UP	1 UP	5600
4x4/164.2	6.7L	5200	5600	1 UP	1 UP	5990
Crew Cab	6.2L	4100	4400	1 UP	2 UP	---
4x2/159.8	6.7L	4550	4850	1 UP	2 UP	---
Crew Cab	6.2L	4400	4700	1 UP	2 UP	---
4x2/176.0	6.7L	5000	5250	1 UP	2 UP	---
Crew Cab	6.2L	4400	4800	1 UP	1 UP	5600
4x4/159.8	6.7L	5200	5600	1 UP	1 UP	5990
Crew Cab	6.2L	4800	5200	1 UP	1 UP	5990
4x4/176.0	6.7L	5600	5600	1 UP	1 UP	5990

Please refer to the Body Builder's Guide for further information regarding front GAWR.

Standard/Optional GVWR for 18" Wheel & Tire

Cab Style/ Drive/WB (in.)	Engine	Front GAWR (lbs.) STANDARD		'Heavy Duty Front Suspension Package (lbs.) 5250-lb. Maximum (4x2) 5990-lb. Maximum (4x4)	Camper Package (lbs.) 5250-lb. Maximum (4x2) 5990-lb. Maximum (4x4)	Snow Plow Package (lbs.)
		MINIMUM	MAXIMUM			
Regular Cab	6.2L	3950	4100	1 UP	2 UP	---
4x2/141.6	6.7L	4550	4700	1 UP	2 UP	---
Regular Cab	6.2L	4400	4400	1 UP	1 UP	5600
4x4/141.6	6.7L	4800	5200	1 UP	1 UP	5990
SuperCab	6.2L	3950	4250	1 UP	2 UP	---
4x2/148.0	6.7L	4550	4850	1 UP	2 UP	---
SuperCab	6.2L	4250	4550	1 UP	2 UP	---
4x2/164.2	6.7L	4850	5000	1 UP	2 UP	---
SuperCab	6.2L	4400	4800	1 UP	1 UP	5600
4x4/148.0	6.7L	5200	5200	1 UP	1 UP	5990
SuperCab	6.2L	4800	4800	1 UP	1 UP	5600
4x4/164.2	6.7L	5200	5600	1 UP	1 UP	5990
Crew Cab	6.2L	4100	4400	1 UP	2 UP	---
4x2/159.8	6.7L	4700	4850	1 UP	2 UP	---
Crew Cab	6.2L	4400	4700	1 UP	2 UP	---
4x2/176.0	6.7L	5000	5250	1 UP	2 UP	---
Crew Cab	6.2L	4400	4800	1 UP	1 UP	5600
4x4/159.8	6.7L	5200	5600	1 UP	1 UP	5990
Crew Cab	6.2L	4800	5200	1 UP	1 UP	5990
4x4/176.0	6.7L	5600	5600	1 UP	1 UP	5990

Please refer to the Body Builder's Guide for further information regarding front GAWR.

2017 SUPER DUTY F-SERIES TRUCKS
Front GAWR Selection Chart

3/24/2017

F-350 DRW Pickup/Pickup Box Delete[2]

The standard front spring/GAWR[1] on pickup models is computer-selected based on the total front weight of options ordered. Front spring/GAWR upgrades are in increments of 150 lbs. on 4x2 models with spring ratings from **3800 lbs.** to 5250 lbs. and in increments of 400 lbs. on 4x4 models with spring ratings from 4400 lbs. to 6000 lbs. Certain option packages include the following front spring/GAWR upgrades:

Heavy Service Suspension Package	Front springs/GAWR will be selected 1 upgrade higher than standard computer selection
Camper Package	4x2: Front springs/GAWR will be selected 2 upgrades higher than standard computer selection 4x4: Front springs/GAWR will be selected 1 upgrade higher than standard computer selection
	Front springs/GAWR is assigned or specifically selected as shown in the chart below.

Front spring/GAWR upgrade is not included if the maximum front spring has been computer-selected as a consequence of options ordered.

Cab Style/ Drive/WB (in.)	Engine	Front GAWR (lbs.) STANDARD		Heavy Duty Front Suspension Package (lbs.) 5250-lb. Maximum (4x2) 5990-lb. Maximum (4x4)	Camper Package (lbs.) 5250-lb. Maximum (4x2) 5990-lb. Maximum (4x4)	Snow Plow Package (lbs.)
		MINIMUM	MAXIMUM			
Regular Cab	6.2L	3950	4100	1 UP	2 UP	---
4x2/141.6	6.7L	4550	4700	1 UP	2 UP	---
Regular Cab	6.2L	4400	4800	1 UP	1 UP	5600
4x4/141.6	6.7L	5200	5200	1 UP	1 UP	5990
SuperCab	6.2L	4250	4400	1 UP	2 UP	---
4x2/164.2	6.7L	5000	5250	1 UP	2 UP	---
SuperCab	6.2L	4800	5200	1 UP	1 UP	5990
4x4/164.2	6.7L	5600	5600	1 UP	1 UP	5990
Crew Cab	6.2L	4400	4700	1 UP	2 UP	---
4x2/176.0	6.7L	5000	5250	1 UP	2 UP	---
Crew Cab	6.2L	5200	5200	1 UP	1 UP	5990
4x4/176.0	6.7L	5600	5600	1 UP	1 UP	5990

F-350 DRW Pickup Box Delete (13,000 lbs. GVWR)[2]

Cab Style/ Drive/WB (in.)	Engine	FRONT GAWR (lbs.) STANDARD		Heavy Duty Front Suspension Package (lbs.) 5250-lb. Maximum (4x2) 5990-lb. Maximum (4x4	Snow Plow Package (lbs.)
		MINIMUM	MAXIMUM		
Regular Cab 4x2/141.5	6.7L	4700	5250	1 UP	-
Regular Cab 4x4/141.5	6.7L	5200	5990	1 UP	5990
Super Cab 4x2/164.1	6.7L	5250	5250	1 UP	-
Super Cab 4x4/164.1	6.7L	5600	5990	1 UP	5990
Chassis Cab 4x2/175.9	6.7L	5250	5250	1 UP	-
Chassis Cab 4x4/175.9	6.7L	5600	5990	1 UP	5990

(1) Gross Axle Weight Rating is determined by the rated capacity of the minimum component of the axle system (axle, computer-selected springs, wheels, tires) of a specific vehicle. Front and rear GAWRs will, in all cases, sum to a number equal to or greater than the GVWR for the particular vehicle. Maximum loaded vehicle (including passengers, equipment and payload) cannot exceed the GVW rating or GAWR (front or rear).

(2)The spring selection process also applies to F-250 and F-350 SRW.

Please refer to the Body Builder's Guide for further information regarding front GAWR.

2017 SUPER DUTY F-SERIES TRUCKS

FRONT GAWR SELECTION CHARTS

3/24/2017

F-450 Pickup - Standard GVWR

Cab Style/ Drive/WB (in.)	Engine	Front GAWR (lbs.) STANDARD		Heavy Duty Front Suspension Package (lbs.) 1 UP	Camper Package (lbs.) 1 UP	Snow Plow Package (lbs.)
		MINIMUM	MAXIMUM			
Crew Cab 4x4 /176.0	6.7L	5600	6000	6000	6000	6000

2017 SUPER DUTY F-SERIES TRUCKS

FRONT GAWR SELECTION CHARTS

3/24/2017

F-350 SRW Chassis Cabs - Standard GVWR

Cab Style/ Drive/WB (in.)	Engine	GVWR Standard/ Optional (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[(1)] (lbs.)	Snow Plow Package (lbs.)
Regular Cab	6.2L	9800	4100	4250	4400	---	---	---
4x2/145.3	6.7L	9800	4700	4850	5000	5250	5250	---
Regular Cab	6.2L	9800	4400	4800	5200	---	---	5600
4x4/145.3	6.7L	9800	5200	5600	5990	5990	5990	5990
SuperCab	6.2L	9800	4400	4550	4700	---	---	---
4x2/167.9	6.7L	9800	5000	5250	5250	5250	5250	---
SuperCab	6.2L	9800	4800	5200	5600	----	----	5990
4x4/167.9	6.7L	9800	5600	5990	5990	5990	5990	5990
Crew Cab	6.2L	9800	4550	4700	4850	----	----	---
4x2/179.8	6.7L	9800	5250	5250	5250	5250	5250	---
Crew Cab	6.2L	9800	5200	5600	5990	----	----	5990
4x4/179.8	6.7L	9800	5600	5990	5990	5990	5990	5990

F-350 SRW Chassis Cabs - 10,000-lb. GVWR

Cab Style/ Drive/WB (in.)	Engine	GVWR Standard/ Optional (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[(1)] (lbs.)	Snow Plow Package (lbs.)
Regular Cab	6.2L	10,000	4100	4250	4400	---	---	---
4x2/145.3	6.7L	10,000	4700	4850	5000	5250	5250	---
Regular Cab	6.2L	10,000	4400	4800	5200	---	---	5600
4x4/145.3	6.7L	10,000	5200	5600	5990	5990	5990	5990
SuperCab	6.2L	10,000	4400	4550	4700	---	---	---
4x2/167.9	6.7L	10,000	5250	5250	5250	5250	5250	---
SuperCab	6.2L	10,000	4800	5200	5600	----	----	5990
4x4/167.9	6.7L	10,000	5600	5990	5990	5990	5990	5990
Crew Cab	6.2L	10,000	4550	4700	4850	----	----	---
4x2/179.8	6.7L	10,000	5250	5250	5250	5250	5250	---
Crew Cab	6.2L	10,000	5200	5600	5990	----	----	5990
4x4/179.8	6.7L	10,000	5600	5990	5990	5990	5990	5990

F-350 SRW Chassis Cabs - Variable GVWR

Cab Style/ Drive/WB (in.)	Engine	GVWR (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[(1)] (lbs.)	Snow Plow Package (lbs.)
Regular Cab	6.2L	10,500	3950	4100	4250	---	---	---
4x2/145.3	6.7L	11,100	4550	4700	4850	5250	5250	---
Regular Cab	6.2L	10,900	4400	4800	5200	----	----	5600
4x4/145.3	6.7L	11,500	5200	5600	5990	5990	5990	5990
SuperCab	6.2L	10,900	4400	4550	4700	----	----	---
4x2/167.9	6.7L	11,500	5000	5250	5250	5250	5250	---
SuperCab	6.2L	11,300	4800	5200	5600	----	----	5990
4x4/167.9	6.7L	11,500	5600	5990	5990	5990	5990	5990
Crew Cab	6.2L	11,000	4550	4700	4850	----	----	---
4x2/179.8	6.7L	11,500	5250	5250	5250	5250	5250	---
Crew Cab	6.2L	11,400	4800	5200	5600	----	----	5990
4x4/179.8	6.7L	11,500	5600	5990	5990	5990	5990	5990

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register **voids** the Ford Warranty.

2017 SUPER DUTY F-SERIES TRUCKS

FRONT GAWR SELECTION CHARTS

3/24/2017

F-350 DRW Chassis Cabs

Cab Style/ Drive/WB (in.)	Engine	GVWR (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[(1)] (lbs.)	Snow Plow Package (lbs.)
Regular Cab	6.2L	14,000	4100	4250	4400	----	----	---
4x2/145.3	6.7L	14,000	4700	4850	5000	5250	5250	---
Regular Cab	6.2L	14,000	4700	4850	5000	----	----	---
4x2/169.3	6.7L	14,000	5250	5250	5250	5250	5250	---
Regular Cab	6.2L	14,000	4800	5200	5600	----	----	5990
4x4/145.3	6.7L	14,000	5200	5600	5990	5990	5990	5990
Regular Cab	6.2L	14,000	5200	5600	5990	----	----	5990
4x4/169.3	6.7L	14,000	5600	5990	5990	5990	5990	5990
SuperCab	6.2L	14,000	4550	4700	4850	----	----	---
4x2/167.9	6.7L	14,000	5250	5250	5250	5250	5250	---
SuperCab	6.2L	14,000	4800	5200	5600	----	----	5990
4x4/167.9	6.7L	14,000	5600	5990	5990	5990	5990	5990
Crew Cab	6.2L	14,000	4700	4850	5000	----	----	---
4x2/179.8	6.7L	14,000	5250	5250	5250	5250	5250	---
Crew Cab	6.2L	14,000	5200	5600	5990	----	----	5990
4x4/179.8	6.7L	14,000	5600	5990	5990	5990	5990	5990

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register **voids** the Ford Warranty.

2017 SUPER DUTY F-SERIES TRUCKS

FRONT GAWR SELECTION CHARTS

3/24/2017

F-450 Chassis Cabs - Standard 16,500 lb. & Optional 16,000/15,000 lb. GVWR

Cab Style/ Drive/WB (in.)	Engine	GVWR Standard/ Optional/ Optional (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[1] (lbs.)	Snow Plow Package (lbs.)	Extra Heavy Duty Front End Suspension[2] (lbs.)
Regular Cab 4x2/145.3	6.8L	16,500/16,000/ 15,000	4800/4800/4400	5200/5200/4800	56005600/5200	----	----	6500	7500
	6.7L	16,500/16,000/ 15,000	5200	5600/5600/6000	6000/6000/6500	7000	7000	7000	7500
Regular Cab 4x2/169.3	6.8L	16,500/16,000/ 15,000	5200	5600	6000	----	----	6500	7500
	6.7L	16,500/16,000/ 15,000	6000/5600/5600	6500/6000/6000	7000/6500/6500	7000	7000	7000	7500
Regular Cab 4x2/193.3	6.8L	16,500/16,000/ 15,000	5600	6000	6500	----	----	6500	7500
	6.7L	16,500/16,000/ 15,000	6500/6500/6000	7000/7000/6500	7000	7000	7000	7000	7500
Regular Cab 4x2/205.3	6.8L	16,500/16,000/ 15,000	5600	6000	6500	----	----	6500	7500
	6.7L	16,500/16,000/ 15,000	6500	7000	7000	7000	7000	7000	7500
Regular Cab 4x4/145.3	6.8L	16,500/16,000/ 15,000	4800	5200	5600	----	----	6500	7500
	6.7L	16,500/16,000/ 15,000	5600	6000	6500	7000	7000	7000	7500
Regular Cab 4x4/169.3	6.8L	16,500/16,000/ 15,000	5600/5600/5200	6000/6000/5600	6500/6500/6000	----	----	6500	7500
	6.7L	16,500/16,000/ 15,000	6000	6500	7000	7000	7000	7000	7500
Regular Cab 4x4/193.3	6.8L	16,500/16,000/ 15,000	6000/6000/5600	6500/6500/6000	7000/7000/6500	----	----	6500	7500
	6.7L	16,500/16,000/ 15,000	6500	7000	7000	7000	7000	7000	7500
Regular Cab 4x4/205.3	6.8L	16,500/16,000/ 15,000	6000	6500	7000	----	----	6500	7500
	6.7L	16,500/16,000/ 15,000	6500	7000	7000	7000	7000	7000	7500
SuperCab 4x2/167.9	6.8L	16,500/16,000/ 15,000	4800	5200	5600	----	----	6500	7500
	6.7L	16,500/16,000/ 15,000	5600	6000	6500	7000	7000	7000	7500
SuperCab 4x2/191.9	6.8L	16,500/16,000/ 15,000	5600/5600/5200	6000/6000/5600	65006500/6000	----	----	6500	7500
	6.7L	16,500/16,000/ 15,000	6000	6500	7000	7000	7000	7000	7500
SuperCab 4x4/167.9	6.8L	16,500/16,000/ 15,000	5200	5600	6000	----	----	6500	7500
	6.7L	16,500/16,000/ 15,000	6000/6000/5600	6500/6500/6000	7000/7000/6500	7000	7000	7000	7500
SuperCab 4x4/191.9	6.8L	16,500/16,000/ 15,000	5600	6000	6500	----	----	7000	7500
	6.7L	16,500/16,000/ 15,000	6500	7000	7000	7000	7000	7000	7500
Crew Cab 4x2/179.8	6.8L	16,500/16,000/ 15,000	5200/5200/4800	5600/5600/5200	6000/6000/5600	----	----	6500	7500
	6.7L	16,500/16,000/ 15,000	5600	6000	6500	7000	7000	7000	7500
Crew Cab 4x2/203.8	6.8L	16,500/16,000/ 15,000	5600	6000	6500	----	----	6500	7500
	6.7L	16,500/16,000/ 15,000	6000	6500	7000	7000	7000	7000	7500
Crew Cab 4x4/179.8	6.8L	16,500/16,000/ 15,000	5200	5600	6000	----	----	7000	7500
	6.7L	16,500/16,000/ 15,000	6000	6500	7000	7000	7000	7000	7500
Crew Cab 4x4/203.8	6.8L	16,500/16,000/ 15,000	6000/6000/5600	6500/6500/6000	7000/7000/6500	----	----	7000	7500
	6.7L	16,500/16,000/ 15,000	6500	7000	7000	7000	7000	7000	7500

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register **voids** the Ford Warranty.

2017 SUPER DUTY F-SERIES TRUCKS

FRONT GAWR SELECTION CHARTS

3/24/2017

F-550 Chassis Cabs - Standard/Optional GVWR

Cab Style/ Drive/WB (in.)	Engine	GVWR Standard/ Optional/ Optional (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package(1) (lbs.)	Snow Plow Package (lbs.)	Extra Heavy Duty Front End Suspension(2) (lbs.)
Regular Cab 4x2/145.3	6.8L	18,000/17,500/ 19,000	4800	5200	5600	----	----	6500	7500
	6.7L	18,000/17,500/ 19,500	5200	5600	6000	7000	7000	7000	7500
Regular Cab 4x2/169.3	6.8L	18,000/17,500/ 19,500	5200/5200/5600	5600/5600/6000	**6500**	----	----	6500	7500
	6.7L	18,000/17,500/ 19,500	6000	6500	7000	7000	7000	7000	7500
Regular Cab 4x2/193.3	6.8L	18,000/17,500/ 19,500	6000	6500	7000	----	----	6500	7500
	6.7L	18,000/17,500/ 19,500	6500/6500/ 7000	7000	7000	7000	7000	7000	7500
Regular Cab 4x2/205.3	6.8L	18,000/17,500/ 19,500	6000	6500	7000	----	----	6500	7500
	6.7L	18,000/17,500/ 19,500	6500/6500/ 7000	7000	7000	7000	7000	7000	7500
Regular Cab 4x4/145.3	6.8L	18,000/17,500/ 19,000	4800/4800/5200	5200/5200/5600	5600/5600/6000	----	----	6500	7500
	6.7L	18,000/17,500/ 19,500	5600	6000	6500	7000	7000	7000	7500
Regular Cab 4x4/169.3	6.8L	18,000/17,500/ 19,500	5600	6000	6500	----	----	6500	7500
	6.7L	18,000/17,500/ 19,500	6500/6000/6500	7000/6500/7000	7000	7000	7000	7000	7500
Regular Cab 4x4/193.3	6.8L	18,000/17,500/ 19,500	6000/6000/ 6500	6500/6500/ 7000	7000	----	----	7000	7500
	6.7L	18,000/17,500/ 19,500	7000	7000	7000	7000	7000	7000	7500
Regular Cab 4x4/205.3	6.8L	18,000/17,500/ 19,500	6500/6000/6500	7000/6500/7000	7000	----	----	7000	7500
	6.7L	18,000/17,500/ 19,500	7000	7000	7000	7000	7000	7000	7500
SuperCab 4x2/167.9	6.8L	18,000/17,500/ 19,500	4800/4800/5200	5200/5200/5600	5600/5600/6000	----	----	6500	7500
	6.7L	18,000/17,500/ 19,500	5600/5600/**5600**	6000/6000/**6000**	6500/6500/**7000**	7000	7000	7000	7500
SuperCab 4x2/191.9	6.8L	18,000/17,500/ 19,500	5600	6000	6500	----	----	6500	7500
	6.7L	18,000/17,500/ 19,500	6500/6000/6500	7000/6500/7000	7000	7000	7000	7000	7500
SuperCab 4x4/167.9	6.8L	18,000/17,500/ 19,500	5200	5600	6000	----	----	7000	7500
	6.7L	18,000/17,500/ 19,500	6000	6500	7000	7000	7000	7000	7500
SuperCab 4x4/191.9	6.8L	18,000/17,500/ 19,500	6000	6500	7000	----	----	7000	7500
	6.7L	18,000/17,500/ 19,500	6500	7000	7000	7000	7000	7000	7500
Crew Cab 4x2/179.8	6.8L	18,000/17,500/ 19,500	5200	5600	6000	----	----	6500	7500
	6.7L	18,000/17,500/ 19,500	5600/5600/6000	6000/6000/6500	6500/6500/7000	7000	7000	7000	7500
Crew Cab 4x2/203.8	6.8L	18,000/17,500/ 19,500	5600	6000	6500	----	----	6500	7500
	6.7L	18,000/17,500/ 19,500	6500	7000	7000	7000	7000	7000	7500
Crew Cab 4x4/179.8	6.8L	18,000/17,500/ 19,500	5600/5200/5600	6000/5600/6000	6500/6000/6500	----	----	7000	7500
	6.7L	18,000/17,500/ 19,500	6000/6000/**6000**	6500/6500/**6500**	7000	7000	7000	7000	7500
Crew Cab 4x4/203.8	6.8L	18,000/17,500/ 19,500	6000	6500	7000	----	----	7000	7500
	6.7L	18,000/17,500/ 19,500	6500/6500/**6500**	7000	7000	7000	7000	7000	7500

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register **voids** the Ford Warranty.
(2) Requires 4.30 or 4.88 axle ratio.